

Arolla Aqua **WASH HC**

THE ONE-OF-A-KIND LED WASH LIGHT FOR HIGH CRI AND FLAWLESS WHITES

- **Light Source:**

Custom 960W white LED engine (7000 K) + TrueCurve™ Technology for whites' calibration

- **Output:**

28,000 lm

- **Zoom Range:**

6°-47° linear zoom

- **Shield Family:**

Moving head fixture suitable for outdoors (IP66)

- **CloudIO Ready:**

Fully compatible with CloudIO



When it comes to creating a truly immersive lighting experience, wash lighting fixtures with **high CRI** are your ace in the hole. These fixtures ensure every hue appears as true and vibrant as it would be under natural light. Introducing **Arolla Aqua Wash**


HC, a versatile **LED single-lens wash light** that redefines what a wash light can do. Completing the Arolla Aqua range in the mid/high segment, this fixture combines **exceptional color accuracy** with **cutting-edge features**. Engineered for performance, it delivers

a **uniform, soft beam of light** that's perfect for illuminating large surfaces and creating captivating atmospheres at any event.

Rain or shine, Arolla Aqua Wash HC is ready to perform. With an **IP66 rating**, it's designed for both indoor and outdoor use, ensuring **reliability in any weather**, while delivering uncompromising performance.

At its core is a **960W custom white LED engine (6000K)**, featuring a **high CRI of up to 95**. Arolla Aqua Wash HC integrates **TrueCurve™ innovation**, an RGB LED system that allows **precise calibration of whites** by controlling green and magenta shifts. This ensures consistent, crisp, and clean whites across the rig—essential for applications like broadcasting, film, or live productions.

Arolla Aqua Wash HC guarantees **true-to-life color reproduction**, ensuring that every hue appears as vibrant and accurate as it would under natural light, making it ideal for applications where every detail matters.



WHAT DO YOU WISH FOR?



The **Arolla Aqua** family just got **bigger**:
3 moving heads ready to fulfill your every desire!

Arolla Aqua

Arolla Aqua **LT**

Arolla Aqua **WASH HC**

The versatile optical system offers an adjustable beam angle **from 6° to 47°**, providing flexibility for precise lighting adjustments. For a wider light distribution, simply add the replaceable frost filter to achieve a **smooth 60° beam**. Whether creating dense aerial effects or a soft, even glow, Arolla Aqua Wash HC adapts to any need.

Its **170mm (6.7 in) lens** ensures even light distribution, while the **internal Barndoor system on 2 focal planes** provides precise beam shaping and control, perfect for theatrical settings


where every shadow and highlight counts.

The **advanced CMY color mixing system** offers infinite color combinations, while a **linear CTO** ensures accurate color temperature adjustments, keeping your designs always on point. And with its **remarkable deep red**, Arolla Aqua Wash HC adds depth and drama to any scene.

To top it off, our **Sun Safe protection system** can automatically safeguard your Arolla Aqua Wash HC from harmful sunlight. By adjusting the

fixture's position to avoid direct rays, even without a signal, it prevents heat buildup and protects vital components. It's a smart, reliable way to keep your equipment safe and your show running as planned.

Combining **cutting-edge technology** with **user-focused design**, Arolla Aqua Wash HC is the ideal solution for lighting professionals seeking both **performance** and **versatility**. From its **high-CRI** and **dynamic color control** to its rugged **IP66 body**, it's a wash light designed to inspire and perform.



Arolla Aqua **WASH HC**

MAIN FEATURES

- Light source: custom 960W white LED engine (6000 K) + TrueCurve™ Technology for whites' calibration
- CRI: up to 95
- Output: 28,000 lm
- 170mm (6.7 in) diameter front lens, consisting of high quality, tempered glass lenses
- 6°-47° zoom range
- 16-bit CMY color mixing
- Linear CTO
- 6-color wheel
- Framing system: two focal planes internal barndoor system
- Replaceable heavy frost for wider beam effect (60°)
- 24-bit digital dimmer with 4 user-selectable dimming curves
- Digital stop-strobe effect
- Control protocols: DMX, Art-Net, RDM, sACN, CRMX (by Lumen Radio)
- CloudIO ready: fully compatible with CloudIO
- Operating voltage: 100-240V, 50/60 Hz
- Max power consumption: 1250VA
- 4 user-selectable fans speed modes
- Weight: 37.5 kg (82.7 lbs)
- Size (LxWxH): 450x320x765 mm (17.7x12.6x30.1 in)
- IP66 protection rating (Shield Family)

